

Delock USB Type-C[™] Adapter to HDMI 4K 30 Hz with USB Type-A and USB Type-C[™] PD

Description

This adapter by Delock is suitable for the connection of a **HDMI monitor** to a computer with **USB-C[™]** interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt[™] 3 interface.

USB Power Delivery (USB PD 2.0) support up to 60 watt


The adapter has a USB Type-C[™] Power Delivery port to connect the power supply of the laptop or tablet to charge it.

Note

When used on a smartphone, an additional power supply may be required if the monitor output and a USB memory device are connected at the same time.

Technical details

- Connectors:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C[™] male >
 - 1 x HDMI-A 19 pin female
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female Battery Charging specification BC1.2
 - 1 x USB Type-C[™] Power Delivery female (optional for power supply)
- Chipset: Algoltek AG6310
- DisplayPort 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Input power: 1 x USB Type-C[™] female max. 60 W
- Supports 3D displays
- Supports HDCP 1.4
- USB bus powered
- Plug & Play





Item no. 64091

EAN: 4043619640911 Country of origin: China Package: Retail Box



- Cable length without connectors: ca. 15 cm
- Colour: black

System requirements

- Android 8.0 or above
- Chrome OS 75.0 or above
- Mac OS 10.14.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt[™] 3 port

Package content

USB-CTM to HDMI Adapter + USB Type-A

Images





General

Function:	Plug & Play
Specification:	High Speed HDMI with Ethernet HDCP 1.4
Supported operating system:	Android 8.0 or above Chrome OS 75.0 or above Mac OS 10.14.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit

Interface

Connector 1:	1 x USB 5 Gbps USB Type-C™ male
Connector 2:	1 x HDMI-A female
connector 3:	1 x USB Type-C [™] Power Delivery female
connector 4:	1 x USB 5 Gbps Type-A female - Battery Charging specification BC1.2

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio

Physical characteristics

Housing material:	Plastic
Cable length:	15 cm