

Delock USB Type-C[™] Adapter to HDMI (DP Alt Mode) 4K 60 Hz + HDR – compact design

Description

This adapter by Delock is suitable for the connection of a **HDMI** monitor to a computer with **USB-C™** interface and **DisplayPort** alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



Small sturdy helper

Due to its **small dimensions and its stable metal housing**, this Delock adapter is especially suitable for travelling. Thanks to its small size, the USB adapter fits in every trouser pocket or can be packed together with the laptop or tablet in the bag and used as needed.

Item no. 64119

EAN: 4043619641192 Country of origin: China Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male
 - 1 x HDMI-A 19 pin female
- Chipset: Realtek RTD2172U
- DisplayPort 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- · Transmission of audio and video signals
- Supports HDR
- Supports HDCP 1.4 and 2.2
- USB bus powered
- Plug & Play
- Dimensions (LxWxH): ca. 42 x 22 x 8 mm
- Colour: grey

System requirements

BATASHEET



- Android 9.0 or above
- Chrome OS 83.0 or above
- iPad Pro (3rd Generation) or above
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Windows 8.1/8.1-64/10/10-64
- PC or mobile devices with a free USB Type-CTM or ThunderboltTM 3 port

Package content

• USB-CTM to HDMI adapter

Images







General

| Function: | Plug & Play |
|-----------------------------|--|
| Specification: | DisplayPort 1.2 High Speed HDMI with Ethernet HDCP 1.4 HDCP 2.2 |
| Supported operating system: | Android 9.0 or above Chrome OS 83.0 or above Linux Kernel 5.4 or above Mac OS 10.15.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |

Interface

| Output: | 1 x HDMI-A female |
|---------|----------------------|
| Input: | 1 x USB Type-C™ male |

Technical characteristics

| Chipset: | Realtek RTD2172U |
|----------------------------|---------------------|
| Maximum screen resolution: | 4096 x 2160 @ 60 Hz |
| Signal transmission: | video audio |
| Voltage: | USB bus powered |

Physical characteristics

| Length: | 42 mm |
|---------|-------|
| Width: | 22 mm |
| Height: | 8 mm |
| Colour: | grey |