

Delock USB Type-C™ DP 1.4 Docking Station 4K - HDMI / DP 1.4 / USB 3.2 / LAN / PD 3.0

Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Up to three monitors can be operated simultaneously at the **DisplayPort** and **HDMI** outputs. Four built-in **USB ports** allow the use of peripherals, and connections for **headset** and **Gigabit network** complete the features.

Multi-Stream Transport (MST)

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows **multiple monitors** to be combined into one large display. The maximum resolution for simultaneous playback on two or three monitors depends on the system and connected hardware.

USB Power Delivery (USB PD 3.0) support up to 85 watt

The docking station has a USB Type-C™ Power Delivery port. If this port is connected to the host device, such as the MacBook, it will charge up to **85 watts** during operation.

Stand, security and VESA mounting

The Delock docking station can be operated either **horizontally or vertically**. A stand is included for vertical operation. Further the docking station can also be mounted to a **50 mm VESA bracket**. The corresponding screw threads are provided on the bottom for this purpose.

A safety cable can be attached to the **Kensington socket** to protect the docking station from theft.



Item no. 87746

EAN: 4043619877461

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female >
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-A female - Battery

Charging specification BC1.2

2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female

1 x HDMI-A female

2 x DisplayPort female

1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack

1 x Headset 3.5 mm 4 pin jack

1 x DC jack

- Maximum resolution (depending on the system and the connected hardware):
DisplayPort 1.4 Multi-Stream Transport (MST):
1 display: up to 3840 x 2160 @ 60 Hz
2 or 3 displays: up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Functions: Mirrored or Extended, with Mac OS and Chrome only one monitor can be extended, all others are mirrored
- Supports HDCP 1.4
- Supports HDR
- Output power for host: max. 85 W
- 1 x On / Off switch
- 1 x LED indicator
- Security lock (Kensington Lock) for security cable
- Screw thread for 50 mm VESA holder
- Colour: black
- Dimensions (LxWxH): ca. 190 x 85 x 27 mm

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.37 A
- Output: 20 V / 6.75 A
- Ground outside, plus inside
- Dimensions:
inside: \varnothing ca. 5.0 mm
outside: \varnothing ca. 7.5 mm
length: ca. 12 mm

System requirements

- Chrome OS
- Mac OS 10.14.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free

Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- Power supply
- User manual

Images



General

Supported operating system:	Chrome OS Mac OS 10.14.5 or above Windows 10 32-Bit Windows 10 Mobile Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
-----------------------------	--

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
----------------------------	---------------------

Physical characteristics

Length:	190 mm
Width:	85 mm
Height:	27 mm
Colour:	black