

# Delock Docking Station for MacBook Dual HDMI 4K / PD / Hub

## Description

This docking station by Delock can be connected to a MacBook with two adjacent Thunderbolt™ 3 ports, e.g. the MacBook Pro. **Two monitors** can be operated simultaneously at the HDMI output ports. **Three built-in USB Type-A ports** allows the use of peripherals. With a USB-C™ power supply, laptops such as the MacBook can be charged during operation.

### Advanced monitor setting

The Delock docking station occupies two ports on the MacBook simultaneous; therefor it is possible to display different content on both HDMI ports at the same time. Further it allows multiple monitors to be combined into one large display. Thereby the docking station supports a maximum resolution of up to **4K** per monitor.

### USB Power Delivery (USB PD 3.0) support up to 60 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. The docking station can also be used without a power supply.

### Small sturdy helper

Due to its **small dimensions** and its **sturdy housing**, this Delock docking station is particularly suitable for travelling. It can simply be packed into the bag together with the laptop and used as needed.

## Note

Only one additional external monitor can be connected to MacBook devices with M1, M2 and M3 chipset. MacBook devices with M1 Pro, M2 Pro, M3 Pro and M3 Max chipset can connect two or more additional external monitors. Further information is available at [www.apple.com](http://www.apple.com).



**Item no. 87753**

EAN: 4043619877539

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 2 x USB Type-C™ male
  - 2 x HDMI-A female
  - 3 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  - 1 x USB Type-C™ female (power supply)
- Resolution:
  - Single + Dual:
    - HDMI port 1 up to 3840 x 2160 @ 60 Hz
    - HDMI port 2 up to 3840 x 2160 @ 30 Hz
  - (depending on the system and the connected hardware)
- Transmission of audio and video signals
- USB Power Delivery (PD) 3.0
- Input power: 1 x USB Type-C™ female max. 60 W
- Metal housing
- Colour: grey
- Dimensions (LxWxH): ca. 116.0 x 28.0 x 9.5 mm

---

## System requirements


- MacBook Pro with two adjacent Thunderbolt™ 3 ports

---

## Package content

- Docking station
- User manual

## Images



### Interface

Connector 1:	2 x USB Type-C™ male
Connector 2:	2 x HDMI-A female
connector 3:	3 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
connector 4:	1 x USB Type-C™ female (power supply)

### Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz 3840 x 2160 @ 30 Hz
Voltage:	USB Power Delivery (PD) 2.0

### Physical characteristics

Housing material:	metal
Colour:	grey