

# Delock Wireless Display USB Type-C™ Adapter Full HD - HDMI + VGA with Card Reader and Hub

## Description

This adapter by Delock can be used to **wirelessly** transmit an audio and video signal in **1080p** format **over a range of up to 10 m**. Only the transmitter has to be connected to the USB Type-C™ port of the device and the receiver via **HDMI or VGA** cable to a TV, projector or similar. **Both video outputs can be used at the same time** to display the signal on two displays at the same time.



### Integrated card reader and hub

Two built-in USB Type-A ports allow the use of peripherals, an **SD** and a **Micro SD** slot allow the use of memory cards.

**Item no. 87775**

EAN: 4043619877751

Country of origin: China

Package: Retail Box

### Easy transport

For transport, the transmitter unit can easily be inserted into the receiver unit's deepening, where both parts are held together by a magnet.

### Plug & Play

After connecting the two parts of the device, the connection is automatically established, no drivers need to be installed or settings made.

## Technical details

- Connectors:
  - Transmitter:
    - 1 x USB Type-C™ male
    - 2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
    - 1 x SD slot
    - 1 x Micro SD slot
  - Receiver:
    - 1 x HDMI-A female
    - 1 x VGA female
    - 1 x 3.5 mm 3 pin stereo jack female
    - 1 x USB Type-C™ female (power supply)

- Resolution:  
HDMI up to 1920 x 1080 @ 60 Hz  
VGA up to 1920 x 1080 @ 60 Hz  
(depending on the system and the connected hardware)
- Transmission of audio and video signals
- Functions: Mirrored or Extended; only one monitor can be extended, all others are mirrored
- Bandwidth: 5 GHz, operating range up to 10 m
- It can be used two memory cards at the same time
- Colour: black
- Cable length: ca. 15 cm
- Dimensions transmitter (LxWxH): ca. 111 x 56 x 13 mm
- Dimensions receiver (LxWxH): ca. 115 x 61 x 22 mm

---

## System requirements

- Android 10.0 or above
- iPad Pro (2018)
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Surface Pro 7
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port
- A free USB Type-A female port (power supply)

---

## Package content

- Transmitter
- Receiver
- USB power cable, length: ca. 0.8 m
- User manual

## Images



## General

Supported operating system:	Linux Kernel 5.4 or above Mac OS 10.15.6 or above Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) Android 10.0 or above
-----------------------------	---

## Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x SD slot 1 x Micro SD Slot 1 x HDMI-A female 1 x VGA female 2 x USB 5 Gbps Type-A female
Input:	1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male

## Technical characteristics

Maximum screen resolution:	1920 x 1080 @ 60 Hz
----------------------------	---------------------

## Physical characteristics

Housing material:	Plastic
Cable length:	15 cm
Colour:	black